



Mirafi[®] RS580*i*

This is to certify that Mirafi[®] RS580*i* is a revolutionary geotextile created from super hightenacity polypropylene filaments formed into an innovative weave to provide superior reinforcement strength and soil interaction integrated with high water flow and soil retention capabilities.

Mechanical Properties	Test Method	Unit	Minimum Average Roll Value	
			MD	CD
STRENGTH				
Tensile Modulus @ 2% strain	ASTM D 4595	kN/m (lbs/ft)	350 (24000)	1313 (90000)
HYDRAULIC				
Flow Rate	ASTM D 4491	l/min/m ² (gal/min/ft ²)	3056 (75)	
Permittivity	ASTM D 4491	sec ⁻¹	1.0	
SOIL RETENTION				
Apparent Opening Size (AOS) ¹	ASTM D 4751	mm (U.S. Sieve)	0.43 (40)	
SOIL INTERACTION				
Interaction Coefficient ²	ASTM D 5321		0.9	
Factory Seam Strength	ASTM D 4884	kN/m (lbs/ft)	43.8 (3000)	
UV Resistance (at 500 hours)	ASTM D 4355	% strength retained	80	

¹ ASTM D 4751: AOS is a Maximum Opening Diameter Value ² Interaction Coefficient value is for sand or gravel

Physical Properties	Unit	Typical Value
Roll Dimensions (width x length)	m (ft)	4.5 (15) x 91 (300)
Roll Area	m² (yd²)	418 (500)
Estimated Roll Weight	kg (lbs)	188 (415)

Disclaimer: TenCate assumes no liability for the accuracy or completeness of this information or for the ultimate use by the purchaser. TenCate disclaims any and all express, implied, or statutory standards, warranties or guarantees, including without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to any equipment, materials, or information furnished herewith. This document should not be construed as engineering advice.





FGS000703 ETQR1 Patent Pending