



Chad Lipscomb, PE, CPESC  
Director, Technical Services  
Western Excelsior Corporation  
PO Box 270308  
Fort Collins, CO 80527-0308  
970-631-8366 office  
chad@westernexcelsior.com

"Blanketing Nature With Nature"

---

Effective: 05/31/11

RE: Certificate of Conformance: Aspen Excelsior Logs™

To Whom it May Concern:

This letter is to certify that Western Excelsior manufactures the product marketed as Western Excelsior Aspen Excelsior Sediment Control Log. Each log is subjected to Western Excelsior's Quality Assurance Program and is manufactured to the specifications listed in document # WE\_EXCEL\_AEL\_SPEC. A copy of the specification document is attached. Installation instructions are provided in document # WE\_EXCEL\_LOG\_II. If you have any questions regarding the installation, use or properties of the sediment control log, please feel free to contact me.

Regards,

A handwritten signature in black ink, appearing to read "Chad M. Lipscomb".

Chad M. Lipscomb, PE, CPESC  
Director, Technical Services  
Western Excelsior Corporation

# MATERIAL PROPERTIES AND DIMENSIONS



## ASPEN EXCELSIOR LOGS™



## Specifications

Western Excelsior manufactures Aspen Excelsior Logs in addition to a full line of Rolled Erosion Control Products (RECPs). Aspen Excelsior Sediment Control Logs consist of a machine produced High Altitude Rocky Mountain Aspen Excelsior Matrix confined by a synthetic net to form a log of specific length and diameter. Aspen Excelsior Logs are designed to reduce hydraulic energy and filter sediment laden flow in channels and on slopes. The logs are flexible to conform to the soil surface and are secured by staking. Aspen Excelsior Sediment Logs can be ordered in custom lengths to meet specific job conditions.

Each Aspen Excelsior Log is manufactured under Western Excelsior's Quality Assurance Program to ensure a continuous distribution of fibers and consistent dimensions. Log dimensions are provided in Table 1 and product characteristics are provided in Table 2. Installation instructions and performance data are available from Western Excelsior's Technical Support Division.

Table 1 - Specified Expected Values

Diameter	10 ft (3.0 m) Length	20 ft (6.0 m) Length	25 ft (7.6 m) Length
9 in (0.23 m)	25.0 lbs (11.3 kg) 2.5 lbs/ft (3.7 kg/m) 5.8 lbs/ft <sup>3</sup> (93.3 kg/m <sup>3</sup> )	50.0 lbs (22.7 kg) 2.5 lbs/ft (3.7 kg/m) 5.7 lbs/ft <sup>3</sup> (92.2 kg/m <sup>3</sup> )	62.5 lbs (28.4 kg) 2.5 lbs/ft (3.7 kg/m) 5.7 lbs/ft <sup>3</sup> (91.9 kg/m <sup>3</sup> )
12 in (0.31 m)	30.0 lbs (13.6 kg) 3.0 lbs/ft (4.5 kg/m) 4.0 lbs/ft <sup>3</sup> (63.5 kg/m <sup>3</sup> )	60.0 lbs (27.2 kg) 3.0 lbs/ft (4.5 kg/m) 3.9 lbs/ft <sup>3</sup> (62.5 kg/m <sup>3</sup> )	75.0 lbs (34.0 kg) 3.0 lbs/ft (4.5 kg/m) 3.9 lbs/ft <sup>3</sup> (62.3 kg/m <sup>3</sup> )
18 in (0.46 m)	50.0 lbs (22.7 kg) 5.0 lbs/ft (7.4 kg/m) 3.0 lbs/ft <sup>3</sup> (47.9 kg/m <sup>3</sup> )	100.0 lbs (45.4 kg) 5.0 lbs/ft (7.4 kg/m) 2.9 lbs/ft <sup>3</sup> (46.7 kg/m <sup>3</sup> )	125.0 lbs (56.7 kg) 5.0 lbs/ft (7.4 kg/m) 2.9 lbs/ft <sup>3</sup> (46.4 kg/m <sup>3</sup> )
20 in (0.51 m)	50 lbs (22.7 kg) 5.0 lbs/ft (7.4 kg/m) 2.4 lbs/ft <sup>3</sup> (39.0 kg/m <sup>3</sup> )	100.0 lbs (45.4 kg) 5.0 lbs/ft (7.4 kg/m) 2.4 lbs/ft <sup>3</sup> (37.9 kg/m <sup>3</sup> )	125.0 lbs (56.7 kg) 5.0 lbs/ft (7.4 kg/m) 2.3 lbs/ft <sup>3</sup> (37.7 kg/m <sup>3</sup> )

Table 2 - Netting

Fiber Composition	High Altitude Machine Curled Aspen Excelsior
Fiber Dimensions	80% Greater than 6 in.
Netting	0.50" x 0.50" Heavy Duty Synthetic
Configuration	Cylindrical with Closed Ends
End Closure	Hog Ring or Tied

\*All values shown measured at the time of manufacture.

Document # WE\_EXCEL\_AEL\_SPEC. This document has been developed to provide the characteristic properties of the product described and supersedes all previous versions. For question, to request performance data or installation recommendations, contact Western Excelsior at 8001-967-4009 or wexcotech@westernexcelsior.com. Updated 05/31/11.